

# Outdoor distribution cabinet

24U STZ 1464/625/625 IP56



ID: 4711

Aluminium cabinet 24U for telecommunication equipment, designed for mounting on SK-1 cable chambers or Fibertechnic plinth 600x600.

**The construction is all-aluminium, rustproof and light, weighs only 39kg. Thanks to those features this is the best alternative to heavy, prone to rust steel cabinets.**

Perfect for FTTX solutions. Cabinet protects devices mounted inside against unauthorized access and hazardous environmental conditions. IP rating IP56, IK rating IK09.

Inside there are 19" RACK rails 24U with adjustment front/back of 148,5 mm.

Top part of the cabinet has dedicated space for mounting panel with fans. Removable floor has cable holes ( dia. 27mm and dia. 45mm). Floor has also M5 filters.

Metal hinges are protected against opening from the outside. Doors sealed using rubber seals and closed with brass lock, also sealed by polymer seal.

Small roof sticks out roughly 0.5cm outside the front of the cabinet. It contains secured vent holes and M5 filters.

Filters should be inspected every 3 months (depends on conditions):

- lower (floor) filter - every 6-9 months
- upper filter – every 18 months

Replacement filters available from cabinet manufacturer.  
IP rating: IP56, IK rating: IK09.

M5 filters- patent pending P.422067

Height [mm]	1464
Width [mm]	625
Depth [mm]	625
Holes	2x dia.27, 1x dia. 45.
Lock	1
Internal dimensions [mm]	1420 x 606 x 576
Doors [pcs]	1
Weight [kg]	43
IP rating	IP56
IK rating	IK09
Material	Powder coated aluminium RAL7035
EAN Code	5902537381872