

Outdoor distribution cabinet 30U, IP56

STZ
1729/816/625

Description

Outdoor distribution cabinet 30U z IP56 STZ 1729/816/625. Dimensions 1729/816/625mm (HxWxD). Ingress protection rating IP56. Mounting on plinth 600x600 or cable manhole.

All aluminium outdoor RACK cabinet. Rust resistant. Tough. Light. Weighs only 49kg and it is the best alternative to heavy, rust prone steel cabinets.

Perfect for FTTX solutions. Cabinet protects devices mounted inside against unauthorized access and hazardous environmental conditions. IP rating IP56, IK rating IK10.

Inside there are 19" RACK rails 30U with adjustment front/back of 135 mm.

Top part of the cabinet has dedicated space for up to 4 wents on special mounting plates. Removable floor has cable holes with possibility of using cable glands (dia. 27mm and dia. 45mm). Floor has also M5 filters.

Metal hinges are protected against opening from the outside. Doors sealed using rubber seals and they are closed using two brass locks, also sealed by polymer seal.

Small roof sticks out roughly 0.5cm outside the front of the cabinet. It contains secured vent holes and M5 filters.

Filters should be inspected every 3 months (depends on conditions):

- lower (floor) filter - every 6-9 months
- upper filter – every 18 months

Replacement filters available from cabinet manufacturer.

IP rating: IP56, IK rating: IK10.

M5 filters- patent pending P.422067



Technical Specification

Height:	1729 mm
Width:	816 mm
Depth:	625 mm
Holes:	2x dia.27, 1x dia. 45.
Lock:	1 x
Internal dimensions:	1420 x 761 x 576 mm(H x W x D)
Doors:	1 x
Weight:	49 kg
IP rating:	IP 56
IK rating:	IK 10
Material:	Powder coated aluminium, RAL7035