Outdoor dual access distribution cabinet
IP56 18U STZD 1196/816/625

≡►FiberTechnic®

CE

ID: 5023

All-aluminium distribution cabinet for telecommunication 18U STZD 1196/816/625 19" dual access with IP56. To be mounted on aluminium or steel base.

Thanks to all-aluminium construction, presented solution is rustproof and light, weighs only 39,6kg. Thanks to those features this is the best alternative to heavy, prone to rust steel cabinets.

Outdoor distribution cabinet IP56 18U STZD 1196/816/625 dual access is designed for FTTX use mailny for protecting most valuable parts of the network like ONT devices, fiber patch pannels, splitters. Perfect solution for setting up telecoms CATV or CCTV equipment or networks FTTX.

Inside the case there are adjustable 19" RACK (adjustable front and back) rails for mounting all the devices, fiber patch pannels and so on. At the top part there is mounting space dedicated for fan pannel, at the bottom there is removable floor has cable holes (dia. 27mm and dia. 45mm). Floor has also M5 filters. Metal hinges are protected against opening from the outside. Doors sealed using rubber seals and they are closed using two brass locks, also sealed by polymer seal.

Thanks to innovative filter cassette with the patent number P.422067, the IP rating is IP56. Filters should be inspected every 3 months (depends on conditions) and replaced:
• lower (floor) filter - every 6-9 months
• upper filter – every 18 months

Replacement filters aviable from cabinet manufacturer.

Ingress protection rating: IP56, impact protection rating IK10.

Warranty period: aluminium 25 years

Wysokość	1196mm
Szerokość	816mm
Głębokość	625mm
Waga	39,6kg
Zamek hermetyczny	2 szt
Drzwi	2 pary
Przepust typu MOREK MC3/7	1 szt.
Klasa szczelności	IP56
Odporność mechaniczna	IK10
Materiał	Aluminium PA11 RAL 7035
Waga	70 kg

cyberteam®