

Outdoor distribution cabinet 30U OP56 STZ

1729/625/816 thermally insulated with electrical switchboard



ID: 6790

All aluminium outdoor RACK cabinet. Rust resistant. Tough. Light. Weighs only 49kg and it is the best alternative to heavy, rust prone steel cabinets.

Perfect for FTTX solutions. Cabinet protects devices mounted inside against unauthorized access and hazardous environmental conditions. IP rating IP56, IK rating IK09.

Inside there are 19" RACK rails 30U with adjustment front/back of 135 mm.

Top part of the cabinet has dedicated space for up to 4 vents on special mounting plates. Removable floor has cable holes with possibility of using cable glands (dia. 27mm and dia. 45mm). Floor has also M5 filters.

Metal hinges are protected against opening from the outside. Doors sealed using rubber seals and they are closed using two brass locks, also sealed by polymer seal.

Small roof sticks out roughly 0.5cm outside the front of the cabinet. It contains secured vent holes and M5 filters.

| | |
|---------------------------|--------------------------------|
| Height | 1729mm |
| Width | 625mm |
| Depth | 816mm |
| Gland holes | 2x dia.27, 1x dia. 45. |
| Lock | 1x |
| Internal dimensions | 1420 x 576 x 761 mm(H x W x D) |
| Doors | 1x |
| Weight | 49kg |
| IP rating | IP56 |
| IK rating | IK09 |
| Material | Aluminium PA11, RAL7035 |
| Corrosion warranty [year] | 25 |