

Thermally insulated outdoor

double shell IP55 hanging cabinet STZT 1052/610/380



ID: 6849

Outdoor double shell insulated aluminium cabinet STZT 1052 mm x 610 mm x 380 mm suitable for mounting on a pole with a dedicated bracket.

Cabinet with mounting plate located on the rear wall. IP55 protection rating.

The cabinet is designed to protect the equipment inside from the harmful effects of external environmental factors and from unauthorised access and activities, including destructive ones.

It allows the installation of heating and ventilation devices to ensure the correct temperature conditions required by the installed equipment. The mounting plate can be used for any type of connector and fibre-optic device.

Key features:

- width 610 mm
- depth 380 mm
- door insulation - 20 mm thick
- insulation layer (in walls)
- wall thickness 30 mm
- weight 35 kg
- handle with hermetic lock, operating panel with three-point locking mechanism
- internal metal hinges - 2 pcs.
- possibility of installing heating and cooling devices
- Cat. M5 filters
- IP55 protection rating
- IK 09 impact resistance

Number of shells	2
Thermal insulation (option) [mm]	30
Thermal insulation (standard) [mm]	20
Height [mm]	1052
Width [mm]	610
Depth [mm]	380
Internal dimensions [mm]	893 x 527 x 279
IP rating	IP55
Material	ALU PA11
Doors [pcs]	1
MOREK	1
Mounting holes [mm]	N/A
Hermetic lock [pcs]	1
Poured polyurethane gasket	√
Colour	RAL7035
Weight [kg]	35
Corrosion warranty [year]	25