

Outdoor distribution cabinet 26U

RACK 21-19" STZD 1467/1381/830mm insulated double-jacket IP56



ID: 7663

Outdoor cabinet with 19" and 21" rack rails 26U STZD 1467/1381/830mm double-jacket IP56 is designed to be used in FTTX applications. Intended to be mounted on a plinth/base.

All-aluminium cabinet for telecommunication equipment. 26U STZD cabinet is made from two parts, first is the plinth / base which is buried in the ground, second is the cabinet itself mounted on the plinth.

Thanks to all-aluminium construction, presented solution is rustproof and light, weighs only 98,0kg. Thanks to those features this is the best alternative to heavy, prone to rust steel cabinets.

The external and internal cabinet construction is made of aluminum (PA-11) with a thickness of 2mm. Insulation layer (in walls) 30mm thick - insulation factor (for 0 C) $\lambda \leq 0,039W / M2 / K$;

Height [mm]	1467
Width [mm]	1381
Depth [mm]	830
Chamber dimensions - upper, left [mm]	700 x 605 x 730 19"
Chamber dimensions - lower, left [mm]	545 x 605 x 730 19"
Chamber dimensions - right [mm]	1250 x 678 x 730 21"
Doors [pcs]	3
Hermetic lock [pcs]	3
Weight [kg]	98
IP rating	IP56
IK rating	IK09 [IK10]
Material	Aluminium PA11
Corrosion warranty [year]	25