

Szafa zewnętrzna

24U STZ IP54 900x600 RAL7033



The entire cabinet body is made of 2mm-thick aluminium, characterised by high corrosion resistance and a low weight of only 49kg.

Inside the cabinet there are steel rack rails with anti-corrosion magnelis coating 30x31x1.5mm with front - back adjustment of 148.5 mm. Cabinet door mounted on external metal hinges - 3 pcs with embedded screws to prevent unscrewing from the outside. Doors locked with brass hermetic lock. Handle with 3-point locking, protected by a poured polyurethane gasket to prevent moisture from entering the cabinet. Cabinet powder-coated (colour RAL7033).

A hole in the top of the cabinet allows a fan panel to be mounted on a dedicated panel (2 or 4 fans). The floor of the cabinet is removable, the floor plate has cable holes (to be punched) Φ 28,8mm, Φ 23mm and Φ 21mm with the possibility of installing glands.

IP Rating of 54. IK Rating of 09.

Rack rail height	24U
Distance between rack rails [inch]	19"
Height [mm]	1464
Width [mm]	915
Depth [mm]	625
IP rating	IP54
IK rating	IK09
Material	Aluminium PA11
Doors [pcs]	1
Mounting holes [mm]	Φ 28,8; Φ 23; Φ 21
Hermetic lock [pcs]	1
Cast polyurethane gasket	yes
Color	RAL7033
Weight [kg]	49
Corrosion warranty [year]	25