

Outdoor distribution cabinet

18U 1196/625/625 dual access IP54



All-aluminium cabinet for telecommunication 18U 1196/625/625 dual access.

Thanks to all-aluminium construction, presented solution is rustproof and light, weighs only 29kg. Thanks to those features this is the best alternative to heavy, prone to rust steel cabinets.

Outdoor cabinet 18U 1196/625/625 dual access is designed for FTTX use mainly for protecting most valuable parts of the network like ONT devices, fiber patch panels, splitters. Perfect solution for setting up telecoms CATV or CCTV equipment or networks FTTX.

Inside the case there are adjustable 19" RACK rails for mounting all the devices, fiber patch panels and so other. At the top part there is mounting space dedicated for fan panel, at the bottom there is removable floor with holes.

Metal hinges are protected against opening from the outside. Doors sealed using rubber seals and they are closed using two brass locks, also sealed by polymer seal.

Ingress protection rating: IP54, impact protection rating IK09 (optional IK10).

Height	1196mm
Width	625mm
Depth	625mm
Weight	29,6kg
Hermetic lock	2 pcs
Doors	2 pcs.
Internal dimensions	1036x606x546mm (H x W x D)
Material	Powder coated aluminium RAL7035
Holes	2pcs f127; 1pc f145
RACK load max.	400kg
IP rating	IP54
IK rating	IK09 (IK10)
Corrosion warranty [year]	25