

Outdoor distribution cabinet

24U STZD 1464/816/625 dual access



Outdoor cabinet 24U STZD 1464/816/625 dual access is designed to be used in FTTX applications.

All-aluminium cabinet for telecommunication equipment. 24U STZD cabinet is made from two parts, first is the plinth which is buried in the ground, second is the cabinet itself mounted on the plinth.

Thanks to all-aluminium construction, presented solution is rustproof and light, weighs only 34kg. Thanks to those features this is the best alternative to heavy, prone to rust steel cabinets.

Outdoor cabinet 24U STZD 1464/816/625 dual access is designed for FTTX use, mainly for protecting most valuable parts of the network like ONT devices, fiber patch panels, splitters.

Inside the case there are adjustable RACK rails for mounting all the devices, fiber patch panels and so other. At the top part there is mounting space dedicated for fan panel, at the bottom there is removable floor with holes.

Metal hinges are protected against opening from the outside. Doors sealed using rubber seals and they are closed using two brass locks, also sealed by polymer seal.

Ingress protection rating: IP54, impact protection rating IK09.

Rack rail height	24U
Distance between rack rails [inch]	19"
Height [mm]	1464
Width [mm]	816
Depth [mm]	625
IP rating	IP54
IK rating	IK09
Material	ALU
Maximum load [kg]	400
Doors [pcs]	2
Mounting holes [mm]	1 x Ø28,8 3 x Ø23 1 x Ø21
Hermetic lock [pcs]	2
Air filter efficiency [m3/h/m2]	5400 / IP54 / DIN43438 EN779
Cast polyurethane gasket	2
Color	RAL7035
Weight [kg]	39,5
Corrosion warranty [year]	25