

# Outdoor distribution cabinet

STZD 35U 805/624 thermo-insulated dual access IP55



ID: 9772

Outdoor cabinet STZD 35U 805/624 thermo-insulated dual access IP55 is designed to be used in FTTX applications.

All aluminium outdoor RACK cabinet. Rust resistant. Tough. Light. Weighs only 55kg and it is the best alternative to heavy, rust prone steel cabinets.

Perfect for FTTX solutions. Cabinet thermo-insulated dual access protects devices mounted inside against unauthorized access and hazardous environmental conditions. IP rating IP55, IK rating IK09.

Inside there are 19" RACK rails 35U with adjustment front/back of 148,5 mm.

Top part of the cabinet has dedicated space for up to 4 wents on special mounting plates.

Outdoor cabinet 35U STZD 816/625 dual access thermo-insulated is designed for FTTX use, mainly for protecting most valuable parts of the network like ONT devices, fiber patch pannels, splitters.

Inside the case there are adjustable RACK rails for mounting all the devices, fiber patch pannels and so other. At the top part there is mounting space dedicated for fan pannel, at the bottom there is removable floor with holes.

Metal hinges are protected against opening from the outside. Doors sealed using rubber seals and they are closed using two brass locks, also sealed by polymer seal.

Height	1847mm
Width	805mm
Depth	624mm
Multi-hole culvert	4 x 8-16mm, 2 x 24-54mm, 1 x 30-60mm
Hermetic lock	2x
Internal dimensions	1646x787x506mm (wys x szer x gł) (H x W x D)
Doors	2x
Weight	55kg
IP rating	IP55
IK rating	IK09
Material	Aluminium PA11